

AD-A046 452

MARYLAND UNIV COLLEGE PARK COMPUTER SCIENCE CENTER  
RECURSIVE COMPUTATION OF PSEUDOINVERSE FOR APPLICATIONS IN IMAG--ETC(U)  
SEP 77 E V KRISHNAMURTHY

F/6 17/2

AFOSR-77-3271

UNCLASSIFIED

TR-580

AFOSR-TR-77-1252

NL

| OF |

AD  
A046452




END

DATE  
FILMED

12-77


DDC





12

AD A046452



COMPUTER SCIENCE  
TECHNICAL REPORT SERIES



UNIVERSITY OF MARYLAND  
COLLEGE PARK, MARYLAND  
20742

AD No.  
DDC FILE COPY

DDC  
RECEIVED  
NOV 15 1977  
REGISTERED  
D

DISTRIBUTION STATEMENT A  
Approved for public release;  
Distribution Unlimited

ACCESSION 12	
NTIS	Write Section <input checked="" type="checkbox"/>
DOC	Dist. Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION.....	
BY.....	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

12

TR-584

AFOSR-77-3271

September 1977

Approved for public release  
distribution unlimited.

**RECURSIVE COMPUTATION OF PSEUDOINVERSE  
FOR APPLICATIONS IN IMAGE  
RESTORATION AND FILTERING.**

E. V. Krishnamurthy  
Computer Science Center  
University of Maryland  
College Park, MD 20742

Technical rept.,

TR-77-1252

**ABSTRACT**

A bisection-transposition algorithm is described for the recursive computation of the Moore-Penrose inverse of a large matrix.

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)  
NOTICE OF TRANSMITTAL TO DDC  
This technical report has been reviewed and is  
approved for public release IAW AFR 190-12 (7b).  
Distribution is unlimited.  
A. D. BLOSE  
Technical Information Officer

DDC  
RECEIVED  
NOV 15 1977  
D

The support of the Directorate of Mathematical and Information Sciences, U. S. Air Force Office of Scientific Research, under Grant AFOSR-77-3271, is gratefully acknowledged, as is the help of Mrs. Shelly Rowe in preparing this paper. The continued interest and encouragement shown by Azriel Rosenfeld are deeply appreciated.

403 018

LB



1. Definitions

Let  $A$  be a rectangular real  $(m \times n)$  matrix, and  $X$  be a  $(n \times m)$  real matrix satisfying the following conditions ( $t$  denotes transpose):

$$AXA = A \quad (1)$$

$$XAX = X \quad (2)$$

$$(AX)^t = AX \quad (3)$$

$$(XA)^t = XA \quad (4)$$

If  $X$  satisfies only (1) it is called a generalized inverse, and will be denoted by  $A^{g_1} = X$ . [1]; when  $X$  satisfies (1) and (2) we call  $X = A^{g_2}$  a reflexive generalized inverse; when  $X$  satisfies (1), (2), (3) and (4) it is denoted by  $A^+$  and is called the Moore-Penrose pseudoinverse.

The partitioning of a matrix  $A$  into submatrices  $A_1$  and  $A_2$  along the column (or row) direction will be denoted by

$$A = A_1 | A_2 \quad \left( \text{or} \quad \begin{pmatrix} A_1 \\ A_2 \end{pmatrix} \right).$$

## 2. Partitioning Methods

The computation of the pseudoinverse of a large matrix is very important for several applications in image processing and filtering [2]. Since the matrices involved in these problems are very large, it becomes necessary to use block partitioning schemes for this purpose. Unfortunately, however, the various methods used for block partitioning have several theoretical limitations, if one wants to set up a recursive scheme.

For instance, consider the conventional partitioning [1]

$$A = \begin{array}{c|c} A_{11} & A_{12} \\ \hline A_{21} & A_{22} \end{array} \quad (5)$$

where  $A_{11}$ ,  $A_{12}$ ,  $A_{21}$ ,  $A_{22}$  are arbitrary rectangular matrices.

Then

$$A^{g_2} = \left[ \begin{array}{c|c} Q^{g_2} & -Q^{g_2} A_{12} A_{22}^{g_1} \\ \hline -A_{22}^{g_1} A_{21} Q^{g_2} & A_{22}^{g_2} + A_{22}^{g_1} A_{21} Q^{g_2} A_{12} A_{22}^{g_1} \end{array} \right] \quad (6)$$

$$A^+ = \left[ \begin{array}{c|c} Q^+ & -Q^+ A_{12} A_{22}^{g_1} \\ \hline -A_{22}^{g_1} A_{21} Q^+ & A_{22}^+ + A_{22}^{g_1} A_{21} Q^+ A_{12} A_{22}^{g_1} \end{array} \right] \quad (7)$$

$$\text{where } Q = A_{11} - A_{12} A_{22}^{g_1} A_{21} \quad (8)$$

For these expressions to be valid, the following conditions are necessary:

- (i) A should be positive semi-definite for using (6)
- (ii) A should be positive semi-definite and  $\text{Rank } (A) = \text{Rank } (A_{11}) + \text{Rank } (A_{22})$  for using (7).

Therefore, if we want to compute  $A^+$  recursively, by a successive partitioning procedure involving smaller matrices, then at any stage the intermediate partitions or block matrices should also satisfy the above conditions. It is clear that while it is possible to make A positive definite by starting with  $AA^t$  and computing  $A^+$  using the formula

$$A^+ = A^t (AA^t \cdot AA^t)^{g_2} AA^t$$

it cannot always be guaranteed that every further sub-partition would satisfy the above conditions. Therefore, in order to recursively partition A through several stages, we must insure that at least the semi-definiteness condition is satisfied by suitable multiplication. This makes the partitioning procedure very complex.

In order to obviate this difficulty, a recursive bi-section-transposition algorithm is suggested below based on the available results on g-inverses [1]. This algorithm does not depend upon the conditions (i) and (ii) since at any stage either a row or column partitioning of the matrix is carried out (and not both).



### 3. Bisection-Transposition Algorithm

#### a. Principle

Let the given matrix  $A_{r-1}$  ( $m \times n$ ) be partitioned as

$$A_{r-1} = [A_r | B_r]$$

where  $A_r$  ( $m \times s$ ) and  $B_r$  ( $m \times (n-s)$ ) ( $s < n$ ). Then it is easily proved that [1]

$$A_{r-1}^+ = \begin{bmatrix} A_r^+ - A_r^+ B_r (C_r^+ + D_r) \\ C_r^+ + D_r \end{bmatrix} \quad (10)$$

where

$$C_r = (I - A_r A_r^+) B_r \quad (11)$$

$$D_r = (I - C_r C_r^+) Q_r^{-1} B_r^t (A_r^+)^t A_r^+ (I - B_r C_r^+) \quad (12)$$

$$H_r = (I - C_r C_r^+) B_r^t (A_r^+)^t \quad (13)$$

$$P_r = H_r H_r^t \quad (14)$$

$$Q_r = (I + P_r) \quad (15)$$

#### Remarks

(i) When  $A_r$  is non-singular, we get  $C_r = 0$  and  $A_r^+ = A_r^{-1}$  and

$D_r = (I + B_r^t (A_r^+)^t A_r^+ B_r)^{-1} B_r^t (A_r^+)^t A_r^+$ . When  $B_r$  is a column vector,  $C_r$  is also a column vector and hence  $C_r C_r^+ = 1$  and hence  $D_r = 0$ .

Therefore, we get



$$A_{r-1}^+ = \begin{bmatrix} A_r^+ - A_r^+ B_r C_r^+ \\ C_r^+ \end{bmatrix} \quad (16)$$

Equation (16) corresponds to the discrete Kalman filtering equations. (Kalman filtering is used extensively to estimate the internal state variable of a linear system based on noisy measurements of output variables.)

- ii) In (12) and (13) certain matrices need not be conformable; this is taken care of by appending the required zero rows and columns to the smaller matrices [3].

#### b. Algorithm

Let  $A_0$  be the given  $(m \times m)$  matrix and let  $(p \times p)$  be the order to which we finally desire to reduce this matrix. Then the number of partitions involved is  $r = 2 \log_2 \left( \frac{m}{p} \right)$ ; the number of transpositions required is  $(r-1)$ . The algorithm uses any one of the standard procedures for computing

$A_i^+$  [4, 5].

In this algorithm  $\rightarrow$  indicates the partitioning operation and  $\leftarrow$  the use of (10) to obtain the pseudoinverse of the preceding larger matrix.

Step 1: Set  $i = 1$ ;  $A_0 \rightarrow [A_i | B_i]$

Step 2:  $A_i^t \rightarrow [A_{i+1} | B_{i+1}]$

Step 3: Set  $i = i+1$

Step 4: Is  $i \leq r$ ; if yes go to Step 2; otherwise go to Step 5.

Step 5: Set  $j = r$ ; compute  $A_j^+$ .

Step 6:  $(A_{j-1}^t)^+ \leftarrow (A_j | B_j)$ .

Step 7: Set  $j = j-1$

Step 8: Is  $j = 0$ ? If yes, go to Step 9; otherwise go to Step 6.

Step 9: Result =  $A_0^+$ . Stop.

Note:

In partitioning, it is not required to carry out exact bisection of the matrix  $A_i$ ; however, it is convenient to have exact bisection, and to have the order of  $A_0$  be a power of 2.

#### 4. Example

$$A_0 = \begin{bmatrix} 1 & 1 & 0 & 1 \\ 1 & 1 & 1 & 0 \\ 0 & 1 & 1 & 1 \\ 1 & 0 & 1 & 1 \end{bmatrix}$$

$A_0$  is not positive semi-definite and  $r(A_{11}) + r(A_{22}) \neq r(A)$ .

$$\text{If we take } A_1 = \begin{bmatrix} 11 \\ 11 \end{bmatrix} ; A_{12} = \begin{bmatrix} 01 \\ 10 \end{bmatrix}$$

$$A_{21} = \begin{bmatrix} 01 \\ 10 \end{bmatrix} ; A_{22} = \begin{bmatrix} 11 \\ 11 \end{bmatrix} . \text{ Therefore, the classi-}$$

cal four partitioning scheme will fail.

We now use the successive bisection-transposition algorithm; here  $m = 4$ ,  $p = 2$ ,  $r = 2$ .

Take

$$A_1 = \begin{bmatrix} 11 \\ 11 \\ 01 \\ 10 \end{bmatrix} ; B_1 = \begin{bmatrix} 01 \\ 10 \\ 11 \\ 11 \end{bmatrix}$$

$$A_1^t = \begin{bmatrix} 1101 \\ 1110 \end{bmatrix} ; A_2 = \begin{bmatrix} 11 \\ 11 \end{bmatrix} ; B_2 = \begin{bmatrix} 01 \\ 10 \end{bmatrix}$$

$$A_2^+ = \frac{1}{4} \begin{bmatrix} 11 \\ 11 \end{bmatrix}$$

$$C_2 = (I - A_2 A_2^+) B_2 = \frac{1}{2} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}$$



$$C_2^+ = \frac{1}{2} \begin{bmatrix} -1 & -1 \\ 1 & -1 \end{bmatrix}$$

$$H_2 = (I - C_2 C_2^+) B_2^t (A_2^+)^t = \frac{1}{4} \begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}$$

$$P_2 = H_2 H_2^t = \frac{1}{8} \begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix}$$

$$D_2 = (I - C_2^+ C_2) Q^{-1} B_2^t (A_2^t) A_2^+ (I - B_2 C_2^+) = \frac{1}{10} \begin{pmatrix} 1 & 1 \\ 1 & 1 \end{pmatrix}$$

$$A_1^+ = \frac{1}{5} \begin{bmatrix} 1 & 1 & -2 & 3 \\ 1 & 1 & 3 & -2 \end{bmatrix}$$

Using  $A_1^+$ ,  $A_1$  and  $B_1$  we get

$$C_1 = (I - A_1 A_1^+) B_1 = \frac{1}{5} \begin{bmatrix} -4 & 1 \\ 1 & -4 \\ 3 & 3 \\ 3 & 3 \end{bmatrix}$$

$$C_1^+ = \frac{1}{3} \begin{bmatrix} -2 & 1 & 1 & 1 \\ 1 & -2 & 1 & 1 \end{bmatrix}$$

$$[I - C_1^+ C_1] = 0; D_1 = 0$$

and

$$A_0^+ = \frac{1}{3} \begin{bmatrix} 1 & 1 & -2 & 1 \\ 1 & 1 & 1 & -2 \\ -2 & 1 & 1 & 1 \\ 1 & -2 & 1 & 1 \end{bmatrix}$$

5. Concluding Remarks

- (i) The above algorithm is useful when one deals with matrices having certain special block features.
- (ii) A fast algorithm for transposition is available in [6].
- (iii) The numerical stability of the above procedure is not established.

It is well-known that the numerical algorithms for computing pseudoinverses lack numerical stability, and accordingly, error-free exact calculations are desirable [5]; see also [7].

- (iv) The computational complexity of the above algorithm is to be established [8].

## References

- [1] R. M. Pringle and A. A. Rayner, "Generalized Inverses of Matrices", New York, Hafner Publishing Company, 1971.
- [2] W. K. Pratt and F. Davarian, "Fast Computational Techniques for Pseudoinverse and Wiener Image Restoration", IEEE Trans. Comput., Vol. C-26, No. 6, pp. 571-580, June 1977.
- [3] R. E. Cline, "Representations for the Generalized Inverse of a Partitioned Matrix", SIAM J. Appl. Math., Vol. 12, pp. 588-600, September 1964.
- [4] A. Ben Israel and T.N.E. Greville, "Generalized Inverses Theory and Applications", New York, John Wiley, 1974.
- [5] T. M. Rao, K. Subramanian and E. V. Krishnamurthy, "Residue Arithmetic Algorithms for Exact Computation of g-Inverses of Matrices", SIAM J. Num. Analysis, Vol. 13, No. 2, pp. 155-171, April 1976.
- [6] D. C. Van Voorhis, "Comments on a Computer Algorithm for Transposing Non-square Matrices", IEEE Trans. Comput. (Corresp.), Vol. C-26, No. 6, pp. 607-608, June 1977.
- [7] S. L. Campbell, "On the Continuity of the Moore-Penrose and Drazin Generalized Inverses", Lin. Algebra and App., Vol. 18, No. 2, pp. 53-57, February 1977.
- [8] A. V. Aho, J. E. Hopcroft and J. D. Ullman, "The Design and Analysis of Algorithms", Reading, Mass., Addison-Wesley, 1974.



~~UNCLASSIFIED~~

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER <b>AFOSR-TR- 77- 1252</b> ✓	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) <b>RECURSIVE COMPUTQTION OF PSEUDOINVERSE FOR APPLICATIONS IN IMAGE RESTORATION AND FILTERING</b> ✓		5. TYPE OF REPORT & PERIOD COVERED <b>Technical</b>
7. AUTHOR(s) <b>E. V. Krishnamurthy</b>		6. PERFORMING ORG. REPORT NUMBER <b>TR-580</b> ✓
9. PERFORMING ORGANIZATION NAME AND ADDRESS <b>Computer Science Ctr. Univ. of Maryland College Pk., MD 20742</b> ✓		8. CONTRACT OR GRANT NUMBER(s) <b>AFOSR-77-3271</b> ✓
11. CONTROLLING OFFICE NAME AND ADDRESS <b>Math. &amp; Info. Sciences, AFOSR/NM Bolling AFB Wash., DC 20332</b>		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE <b>September 1977</b> ✓
		13. NUMBER OF PAGES
		15. SECURITY CLASS. (of this report) <b>Unclassified</b>
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  <b>Approved for public release; distribution unlimited.</b>		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) <b>Filtering                      Restoration Generalized inverses Moore-Penrose inverse Partitioning Recursive computation</b>		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <b>A bisection-tranposition algorithm is described for the recursive computation of the Moore-Penrose inverse of a large matrix.</b>		